




Passo Series

Recessed Wall Light



Wall recessed luminaire suitable for pathways, stairs, passages or similar applications.

Construction: Die-cast Aluminium with tempered glass lens. IP65. IK09.

Lens: Diffused glass lens 5mm.

Installation: External wall recessed with separate installation frame.

Finish: White, Black or Stainless Steel trim.




LED: 2w to 6w LED. 4000K as standard, 3000K on request.

Driver: Internal, 110/240V AC 50/60Hz.



Options: DALI.

Manufactured: EU.

Product Compliance: EN 60598, CE, UKCA.




Application Guide




DIMENSIONS

Size 1



Size 2



All dimensions in mm

OPTIONS

- 3K: 3000K, Warm White
- .01: White Finish
- .02: Black Finish
- .15: Stainless Steel Trim
- DALI: DALI on request

ORDERING CODE

Wattage	Type	Size	Code	Details	+Frame	Lumens*
2w	LED	1	G1604.BAAT400	Recessed Wall Light, Asymmetric, 4K	GAC503	288 lm
4w	LED	2	G1602.BGAT400	Recessed Wall Light, Asymmetric, 4K	GAC004	576 lm
6w	LED	3	G1602.ETAT400	Recessed Wall Light, Asymmetric, 4K	GAC004	778 lm

*Source lumens