



StreetLED Series

External lighting



Functional modern LED streetlight in 3 sizes and multiple wattages with adjustable mastfitter or wall mounting.

Construction: Aluminium and PMMA. IP66. IK09. Class 1. LEDs and Driver are not accessible for maintenance or replacement. Product not suitable for Marine areas (ie. within 1km of sea).

Installation: Mastfitter for Post top or Side entry mounting. 76mm and 60mm versions available. 76mm typically for Post-top and 60mm for Side Entry. Optional adjustable tilt angle from -15° to + 15°.

Finish: Light Grey RAL 9006 as standard.

Optic: Street Optic as standard. Forward Throw Optic available for selected wattages.

LED: 14w to 167w high power LED 4000K CRI>70 as standard. Other CCT or CRI on request.
Lifetime: L90 B10 100,000 Hours @ 25°C



Driver: 190-264V AC 50/60 Hz. Integrated in luminaire and is not changeable. 4kV Surge protection included.

Manufactured: EU.


Product Compliance: EN 60598; CE.



Veelite


DIMENSIONS

Size	1	2	3
L	430	430	720
W	200	310	465
H	130	135	139
All Dimensions are in mm.			
Windage(m²)	0.036	0.037	0.056



APPLICATION GUIDE

StreetLED Series
46w 4000K Street Optic
6m Height
Contours in Lux
M. Factor = 0.9



ORDERING CODES - LUMINAIRES

Wattage	Type	Code	Size	Details	Weight	Lumens
14w	LED	5LSA05LGA	1	StreetLED with driver	3 kg	1900 lm
17w	LED	5LSA06LGA	1	StreetLED with driver	3 kg	2300 lm
24w	LED	5LSA07LGA	1	StreetLED with driver	3 kg	3100 lm
25w	LED	5LSA10LGA	2	StreetLED with driver	3 kg	3800 lm
32w	LED	5LSA11LGA	2	StreetLED with driver	4 kg	4700 lm
46w	LED	5LSA12LGA	2	StreetLED with driver	4 kg	6200 lm
56w	LED	5LSA13LGA	2	StreetLED with driver	4 kg	7200 lm
69w	LED	5LSA16LGA	3	StreetLED with driver	8 kg	9900 lm
83w	LED	5LSA17LGA	3	StreetLED with driver	8 kg	11400 lm
92w	LED	5LSA19LGA	3	StreetLED with driver	8 kg	13200 lm
111w	LED	5LSA20LGA	3	StreetLED with driver	8 kg	15200 lm
115w	LED	5LSA22LGA	3	StreetLED with driver	8 kg	16500 lm
138w	LED	5LSA23LGA	3	StreetLED with driver	8 kg	19500 lm
167w	LED	5LSA25LGA	3	StreetLED with driver	8 kg	22600 lm

+ ORDERING CODE - MASTFITTERS

-	-	5LST00001	Adjustable Mastfitter 60mm	2 kg
-	-	5LST00002	Adjustable Mastfitter 76mm	2 kg
-	-	5LST00003	Fixed Mastfitter 60mm	1 kg

OPTIONS

D50: With 50% Dimming
DIM: With 1-100% dimming (1-10V)
PC: Photocell
3K: 3000K
FT: Forward Throw Optic (69w, 83w, 92w & 111w only)

Further info on request · email: info@veelite.com · www.veelite.com

Specifications may change without prior notification. Ref: 480

Veelite