




HT HighBay

Internal Lighting



LED HighBay ideal for efficient commercial and Industrial lighting with special options:

- High Temperature (with Vertical Driver)
- High Lumens/Watt (190lm/w)
- Integrated Sensor

Construction: Cold forged Aluminium.
IP65. Centre Section for Sensor - eg. Microwave, Zigbee.

Installation: Suspended via eyebolt.
Flying Lead Provided.

Finish: Black as standard.

LED: 100w - 200w LED.
5000K as standard. 3K or 5K on request.
90° Beam Optic as standard.
(60°/120° on request).
Ambient temperature: -30°C to +50°C.
To 65°C on request.

Life: > 50,000 hours. L70.

Options: Beam Angles, Colour
Temperature, High Temperature, DALI, PIR,
Daylight.

Product Compliance: EN 60598; CE.



DIMENSIONS			
Wattage	Diameter	Height	Weight
100w	360mm	186/309mm	5.5kg
150w	360mm	186/309mm	5.6kg
200w	360mm	186/309mm	5.5kg

ORDERING CODE				
Code	Wattage	Description	Lumens*	HT Lumens
3HTM0100A	100w	LED HighBay with Sensor Option, 90° Beam, 5K	19,000 lm	15,000 lm
3HTM0150A	150w	LED HighBay with Sensor Option, 90° Beam, 5K	28,500 lm	22,500 lm
3HTM0200A	200w	LED HighBay with Sensor Option, 90° Beam, 5K	38,000 lm	30,000 lm

* High Efficiency Version Lumen Output. Lumen output will change depending on optic used.
5K Version provides approx 5% more lumens.

OPTIONS	
3K: 3000K	
4K: 4000K	
DIM: 1-10V Dimming	
HT: High Temp Version (Vertical)	
DALI: DALI	
Daylight: Daylight Sensor	
PIR: PIR Sensor	
60D: 60 Degree Beam	
120D: 120 Degree Beam	